

Tel : 4266953
Fax : 4660179
Date : 08.03.2010



COK İVEDİ

FAX TRANSMISSION - FAX MESAJI

: انقيد
: التاريخ

FROM	/	KİMDEN	:	MISIR SAVUNMA ATAŞELİĞİ
TO	/	KİME	:	SAVUNMA SANAYİ MÜSTEŞARLIĞI
FAX NO	/	FAX NO	:	4119071
DATE	/	TARİH	:	08.03.2010
REFERENCE	/	KONU	:	İHALE BİLDİRİMİ HK.
PAGE	/	SAYFA	:	KAPAK DAHİL 4 SAYFA .

SAVUNMA SANAYİ MÜSTEŞARLIĞI
ANKARA

318 / 10

Mısır A.C. Büyükelçiliği Askeri Ataşe Ofisi saygılarını sunar ve EK'te (16/2010/QM/4) No.lu teklif isteği sunulduğunu, uçaklarda ve arabalarda kullanılan (4 adet) 'İKİ KİŞİLİK SOĞUTMALI TABUT' alanında üretici firmalar tarafından en kısa zamanda bir teklifin 3 adet katalog (ingilizce) halinde (2 adet teknik ve 1 adet fiyat teklif listesi) ve anlaşma şartları aşağıda belirtilen adrese en kısa zamanda sunulmasını aşağıda belirtilen adrese sunulmasını rica eder;

MISIR SAVUNMA ATAŞELİĞİ - ATATÜRK BLV 126 - K.DERE - ANKARA

- | | | | |
|----|------------------------------------|---|-------------------------------|
| 1- | Ücretler Mısır'a ihraç olmak üzere | : | C I P |
| 2- | Ödeme Şekli | : | Akreditif |
| 3- | Mısır'a ihraç olma süresi | : | En kısa zamanda |
| 4- | Eğitim ile ilgili istekler | : | Ek'te olanı |
| 5- | İstenilen kataloglar | : | Teklif e ait özel bir katalog |
| 6- | İnceleme yöntemi | : | Ek'te olanı |
| 7- | İhaleye son katılım tarihi | : | 21.03.2010 |
| 8- | İhalenin geçerli olma süresi | : | 6 Ay |

Kr. Alb. Tarek ELBRIDY
Mısır Savunma Ataşesi

الموصفات الفنية خاصة لتدبير عدد (٤) ثلاجته حفظ الموتى طاقة (٢) جثه لكل ثلاجته تستخدم بالطائرة او

العربات

المواصفه	م
Made of PVC polyurethane or bright polished stainless steel with External corrosion resistant galvanized /stainless steel and stainless steel interior covering.	١
Heat exchange batteries (evaporator and condenser) are built with copper piping; the frame and fins are in aluminium, with ample exchange surface area. The electric fans for the evaporator are totally sealed.	٢
Defrosting with hot gas system and electric resistances avoids the outflow of condensate.	٣
The mobile mortuary comprising: at least one set of forklift pockets for receiving tines of a forklift truck	٤
Temperature within the cooling room must be from Temperature Range: -18° to +5°c with optimum temperature 2-4 °c in all environmental temperatures, refrigeration units designed for use in tropical countries	٥
The mobile mortuary is specifically comprised of four-inch thick rigid, chlorofluorocarbon-free, urethane form-in-place modular panels with 22-gauge embossed Galvalume at least	٦
The mobile mortuary floor is comprised of a one-hundredth of an inch thick aluminum tread plate. The floor will support evenly distribute loads up to 750 pounds per square foot	٧
The mobile mortuary has a shatterproof interior for safety and efficiency	٨
The expansion of the gas is achieved through capillary tube or thermostatic valve.	٩
Use Ecologic gas	١٠
COMPRESSOR: sealed-type compressor with gas aspiration cooling, complete with total protection motor with electronically-controlled thermistors. A three quarter horsepower compressor is to be used on the coolers	١١
The mobile mortuary may be use with AC , Dc a 220 volt, 12 volt. 20 amp shoreline connections, 50/60 hz.	١٢

الموصفات الفنية خاصه لتدبير عدد (٤) ثلاجه حفظ الموتى طاقة (٢) جته لكل

ثلاجه تستخدم بالطائرة او العربات

المواصفه	د
Providing two 220, 12 volt electrical outlets for use as a receptacle for shoreline connection, and at last one cable that can use the airplane power	١٣
The mobile carriage system, by which the cooler is made mobile, is comprised of a trailer frame, two trailer axles, four trailer wheels, and four trailer tires	١٤
Additionally the trailer frame has a heavy-duty double-frame tongue. The two trailer axles are 5,200-pound. Rubber suspension axles, providing independent wheel suspension, rubber cushioning, and shock absorption.	١٥
The mobile mortuary is constructed and designed to be readily shipped to remote field locations by a transport carrier, such as: a helicopter, C130 cargo plane or other aircraft; ship; train; truck; or an all terrain vehicle. For airborne shipment and precision drop placement, the mobile mortuary comprises an impact-resistant composite panel system with sufficient structural strength and integrity to be dropped two feet by a helicopter or parachute without damaging or significantly impairing the operation and use of the containerized field kitchen and its contents.	١٦
The door panel of the mobile mortuary includes a door that is hinged and includes a non positive latch. The door is has a width of 34 inches wide and a height 75 inches. Furthermore, the mobile mortuary door includes a safety mechanism to allow exit from the mobile mortuary even when the mobile mortuary door is padlocked.	١٧
Can work in maximum degree of humidity	١٨
Easy sterilization with supplementation of sterilization and disinfection tools and compounds	١٩
Adjustable thermostat.	٢٠
Programmable min/max operating values	٢١
Choice of manual or automatic defrosting, cycle frequency, time and temperature of defrosting program.	٢٢

الموصفات الفنية خاصة بتدبير عدد (٤) ثلاجه حفظ الموتى طاقة (٢) جثه لكل

ثلاجه تستخدم بالطائرة او العربات

المواصفه	٢
Pause start evaporator ventilator	٢٣
Down time after defrosting to drain discharge water	٢٤
Temperature failure visual and audible alarm.	٢٥
Push button or micro switch operates chamber's interior light.	٢٦
Variable press stat interventions	٢٧
The condensing unit is normally mounted on the roof of the chamber but can be re-sited to suit particular requirements.	٢٨
All rollers are removable for easy cleaning of the interior	٢٩
The refrigerator supplied with mortuary trolley, autopsy table, immersion dissection table, autopsy tools set, mortuary lifter, etc.	٣٠
Body trays: made of heavy gauge stainless steel BS 304 S 15,seamless	٣١
Tray supports: each body-tray positioned on a pair of one end opening mortuary cooling chamber U-shaped rails for easy handling.	٣٢
Loading/Unloading: manually or hydraulic lifting cart	٣٣
Automatic removal of dew water	٣٤
Refrigerating unit: hermetically sealed, air-cooled, vibration-free,	٣٥
Cooling system: fully automatic with build-in automatic defrost, system and evaporator inside (ceiling) of cell.	٣٦
Internal light with switch outside of cell (standard)	٣٧
Telescopic, stainless steel body stretchers	٣٨
Activated-carbon filter air extraction system.	٣٩
The refrigerator has two independent cooling units of air-cooled	٤٠
3-digits high brightness numerical code display, the set value of temperature can be trimmed within a range of -10~10°C, the temperature accuracy and resolution ratio are all 0.1°C	٤١
The contract must include supplying, training for 2 weeks for 6 personnel, instillation , maintenance for the unit	٤٢
There must be 5 years grantee including the supply of all spare parts needed	٤٣
The product must be FDA, Or CE approved with a certificate of approval, and ICAO tested and approved	٤٤